

## Uddeholm Vanadis 10 SuperClean Stock Standard

### Flat bar

Soft annealed/Unmachined ☐

Soft annealed/Rough machined ■

mm	12	15	18	22	28	38	41	50	54	63,5	76,2	90	102	200
30		☐												
57	☐		☐	☐	☐									
108	☐		☐	☐	☐		☐		☐					
153													■	
160					☐				☐					
166		☐												
203										■				
210				☐	☐				☐					
260									☐					
375						■		■		■	■	■	■	
400														■

### Square bar

Soft annealed/Rough machined

mm	200
	■

## Uddeholm Vanadis 10 SuperClean Stock Standard

### Round bar

Soft annealed/Rough machined

mm	18	20	25,4	32	35	40	46	57,2	63,5	70	80	90
	●	●	●	●	●	●	●	●	●	●	●	●

mm	102	110	115	127	140	153	165	180	203	230	254	305	460
	●	●	●	●	●	●	●	●	●	●	●	●	●

### Plate

Width: 1,00-4,99 = 650 mm, 5,00-80,00 = 750 mm

Tolerance: -0 / +200 mm

Length: Random length mm

Soft annealed/Unmachined

Thickness, mm	1,5	4,4	6,5	8,2	16	21	28	34	40
	□	□	□	□	□	□	□	□	□

### Pre-machined

Random length: 1800-2000 mm

Width mm	Thickness mm					
	10	12	16	20	25	50
50	□		□		□	
100				□	□	□
160		□				
200						□