

Uddeholm Vancron 40 Stock Standard

Flat bar

Soft annealed/Rough machined

mm	63,5	76,2	102	153	254
254	■	■	■	■	■

Round bar

Soft annealed/Precision machined

Cold drawn fix length/Tolerance ISO h9

mm	8	10	12,7
	○	○	○

Round bar

Soft annealed/Rough machined

mm	16,2	18	25,4	32	40	50,8	63,5	70	80	90	102	127	140	153	180	203	230	254	280	
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Plate

Width: 650 mm

Tolerance: -0 / +200 mm

Length: Random length mm

Soft annealed/Rough machined

mm	16	21	28	34
	□	□	□	□

Uddeholm Vancron 40 Stock Standard

Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.80 mm

Random length: 1800-2000 mm

Width mm	Thickness, mm					
	15	20	25	32	40	50
130	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
250			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>