

Uddeholm Vanadis® 23 SuperClean

Flachstahl

Breite mm Dicke mm		10	12	15	18	20	22	28	35	40	41	43	50	54	63	76,2	80	100	102	200	
57		□	□	□	□		□	□			□										57
102																	■				102
108			□	□	□		□	□	□			□		□							108
150										□			□		■						150
152,4																■					152,4
158							□	□	□					□							158
203,2																■					203,2
210							□	□	□			□									210
260					□			□						□							260
305																■			■		305
380										■											380
400																				■	400
550																		■			550

□ = unbearbeiteter Stahl ■ = bearbeiteter Stahl

Vierkantstahl

Kantenlänge mm	20	43	50	57	69	86	120
	□	□	□	□	□	□	■

□ = unbearbeiteter Stahl ■ = bearbeiteter Stahl

Rundstahl

Durchmesser mm	4,3	5,3	6,3	7,3	8,3	9,3	10,3	12,3	13,3	15								
	○	○	○	○	○	○	○	○	○	○								
	16	18	20	22	24	26	28	30	32	35	38	40	42	46	50,8	52	54	60
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	63,5	65	70	76,2	80	82,6	85	90	100	102	110	115	120	125	130	140	150	153
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	160	170	180	190	203	210	225	250	270	305	370	420						
	●	●	●	●	●	●	●	●	●	●	●	●						

○ = kaltgezogener Rundstahl geschliffen auf Toleranz h9 ● = bearbeiteter Rundstahl

Bleche

Breite mm Dicke mm		5,2	6,2	9,2	11,2	13,2	21	28	34
650-850		□	□	□	□	□	□	□	

Breite (Produktionsabhängig)

□ = unbearbeiteter Stahl