

Uddeholm Calmax Stock Standard

Flat bar

Soft annealed/Unmachined ☐

Soft annealed/Rough machined ▬

mm	28	35	43	50	54	63	80	100	125	160	200
57	☐										
69		☐									
100						▬	▬				
108	☐	☐	☐		☐						
125						▬	▬				
160						▬	▬				
166	☐	☐	☐		☐						
200						▬	▬				
210	☐	☐	☐		☐						
250						▬	▬	▬			
260	☐	☐	☐		☐						
315				▬		▬	▬	▬	▬	▬	
355				▬				▬	▬		
400						▬	▬	▬	▬	▬	▬
450							▬		▬		
500						▬	▬	▬	▬		▬
600										▬	▬

Uddeholm Calmax Stock Standard

Square bar

Soft annealed/Unmachined □

Soft annealed/Rough machined ■

mm	54	86	100	125	160
	□	□	■	■	■

Round bar

Soft annealed/Unmachined ○

Soft annealed/Rough machined ●

mm	14	18	22	28	35	43	50	55	63	70	80	90	100	125	140	160	180	200	225	250	280	315	355	400	500	
	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Uddeholm Calmax Stock Standard

Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.80 mm
 Length: 1030 mm

Width mm	Thickness mm					
	25	32	40	50	63	80
40	▬					
50	▬					
63	▬	▬				
80						
100	▬	▬	▬	▬		
160		▬	▬	▬		
200			▬			
250			▬			
Square			■	■	■	