

Uddeholm Vanadis 23 SuperClean Stock Standard

Flat bar

Soft annealed/Unmachined ☐

Soft annealed/Rough machined ■

mm	10	12	15	18	20	22	27	28	35	40	41	43	45	50	54	63	76,2	80	100	102	200	
57	☐	☐	☐	☐		☐		☐			☐											
100																						
102																		■				
108		☐	☐	☐		☐		☐	☐			☐			☐							
150										☐				☐		■						
152,4																	■					
158						☐		☐	☐						☐							
203,2																	■					
210						☐		☐	☐			☐										
260					☐			☐							☐							
305																	■				■	
380										■												
400																						■
550																			■			

Square bar

Soft annealed/Unmachined ☐

Soft annealed/Rough machined ■

mm	20	43	50	57	69	86	120
	☐	☐	☐	☐	☐	☐	■

Uddeholm Vanadis 23 SuperClean Stock Standard

Round bar

Soft annealed/Precision machined

Cold drawn fix length/Tolerance ISO h9

mm	4,3	5,3	6,3	7,3	8,3	9,3	10,3	12,3	13,3	15,0
	○	○	○	○	○	○	○	○	○	○

Round bar

Soft annealed/Rough machined

mm	16	18	20	22	24	26	28	30	32	35	38	40	42	46	50,8	52	54	60	63,5	65
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	70	76,2	80	82,6	85	90	100	102	110	115	120	125	130	140	150	153	160	170	180	190
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	203	210	225	250	270	305	370	420
	●	●	●	●	●	●	●	●

Plate

Width: 1,00-4,99 = 650 mm, 5,00-80,00 = 750 mm

Tolerance: -0 / +200 mm

Length: Random length mm

Soft annealed/Unmachined

Thickness, mm	5,2	6,2	9,2	11,2	13,2	21	28	34
	□	□	□	□	□	□	□	□

Uddeholm Vanadis 23 SuperClean Stock Standard

Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.80 mm

Random length: 1800-2000 mm

Width mm	Thickness mm							
	8	10	16	20	25	32	40	50
50	☐	☐	☐	☐				
100		☐	☐	☐	☐	☐	☐	☐
200				☐	☐	☐	☐	
Square								☐