

Uddeholm Stavax ESR Stock Standard

Flat bar

Soft annealed/Unmachined

mm	11	12,7	20	22	25	28	35	38,1	40	43	54
45	☐										
65							☐				
75			☐						☐		
85						☐					
90									☐		
102		☐						☐			
105						☐					
155				☐							
166						☐	☐			☐	☐
206						☐	☐			☐	☐
228					☐						
256						☐	☐			☐	☐
306										☐	

Uddeholm Stavax ESR Stock Standard

Flat bar

Soft annealed/Rough machined

mm	38	40	50	51	63	64	76,2	80	89	90	100	114	127	153	160	178	203	254
102				—														
153							—											
160					—													
200					—			—										
228			—															
250					—			—										
300								—							—			
305	—			—		—	—			—			—	—				
350		—	—		—			—			—							
400		—	—		—			—			—							
450		—						—										
457	—			—		—							—					
500		—	—		—			—										
508																		
600															—			
610							—		—			—	—	—			—	—
762	—					—										—		

Uddeholm Stavax ESR Stock Standard

Round bar

Soft annealed bar/Unmachined 0

Soft annealed bar/Rough machined ●

mm	12,7	16	20	28	35	40	41	43	50,8	57,2	63,5	76,2	80	90	102	115	127	140	153	160	180	203	230	254	
	0	0	0	0	0	●	0	0	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Soft annealed/Precision machined

mm	10	30	45
	●	●	●

Square

Soft annealed/Unmachined

mm	57	75
	□	□

Uddeholm Stavax ESR Stock Standard

Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.8 mm

Length: 1030 mm

mm	30	40	50	60	80	100
100	☐	☐	☐	☐	☐	☐
125	☐	☐	☐	☐	☐	☐
160	☐	☐	☐	☐	☐	☐
200	☐	☐	☐	☐	☐	☐
250		☐	☐	☐	☐	☐
300		☐	☐	☐	☐	☐