

Uddeholm Vanadis 30 SuperClean Stock Standard

Flat bar

Soft annealed/Unmachined

Soft annealed/Rough machined

mm	10	15	20	22	30	35	43	50	54	55	75
45			<input type="checkbox"/>								
95											<input type="checkbox"/>
208				<input type="checkbox"/>	<input type="checkbox"/>						
210							<input type="checkbox"/>		<input type="checkbox"/>		
260						<input type="checkbox"/>	<input type="checkbox"/>				
380								<input checked="" type="checkbox"/>			

Square bar

Soft annealed/Unmachined

Soft annealed/Rough machined

mm	28	102
	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Uddeholm Vanadis 30 SuperClean Stock Standard

Round bar

Soft annealed/Precision machined

Cold drawn fix length

Tolerance ISO h9

mm	4,3	6,3	8,3	10,3	12,3	13,0	14,0	15,0
	●	●	●	●	●	●	●	●

Round bar

Soft annealed/Rough machined

mm	16	18	20	22	26	30	35	40	46	48	52	60	70	82,6	85	110	130	140	150	160	170	290	
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●