

Uddeholm Elmax SuperClean Stock Standard

Flat bar

Soft annealed/Rough machined

| mm | 32 | 50 | 60 | 63 | 65 | 102 | 200 |
|-----|----|----|----|----|----|-----|-----|
| 133 | | | ▬ | | | | |
| 185 | | | | | ▬ | | |
| 254 | | | | | | ▬ | |
| 300 | ▬ | | | | | | |
| 304 | | ▬ | | | | | |
| 400 | | | | ▬ | | | ▬ |

Round bar

Soft annealed/Rough machined

| mm | 15 | 20 | 28 | 32 | 35 | 38 | 42 | 46 | 50,8 | 57,2 | 63,5 | 60 | 76,2 | 80 |
|----|----|----|----|----|----|----|----|----|------|------|------|----|------|----|
| | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |

| mm | 102 | 115 | 127 | 140 | 153 | 180 |
|----|-----|-----|-----|-----|-----|-----|
| | ● | ● | ● | ● | ● | ● |

Plate

Width: 1,00-4,99 = 650 mm, 5,00-80,00 = 750 mm

Tolerance: -0 / + 200 mm

Length: Random length mm

Soft annealed/Unmachined

| Thickness, mm | 2,5 | 3,78 | 4,56 | 5,2 | 5,94 | 6,76 | 15,2 |
|---------------|-----|------|------|-----|------|------|------|
| | ▬ | ▬ | ▬ | ▬ | ▬ | ▬ | ▬ |

Uddeholm Elmax SuperClean Stock Standard

Fine Machined
Flat bar
Random length

| mm | 12 | 16 | 20 | 25 | 32 | 40 | 50 |
|-----|----|----|----|----|----|----|----|
| 160 | | ■ | | | | | |
| 200 | ■ | ■ | ■ | ■ | ■ | | |
| 250 | | | | | | ■ | ■ |
| 300 | | | | | | | ■ |