

Uddeholm UHB 11 Stock Standard

Square bar
Hot worked/Unmachined

mm	130
	£

Round bar
Hot worked/Unmachined ○
Hot worked/Rough machined ●

mm	22	32	35	40	45	50	60	65	70	80	100	125	150	160	180	200	230	250	300	330	350	450	
	○	○	○	○	○	○	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●

Plate
Hot worked/Unmachined
Width: 2075 mm

mm	6	8	10	12	15	19	23	28	35	43	45	48	53	58	63	66	75	83	86	90	
	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□

mm	103	110	120	128	140	150	165	180	200	250
	□	□	□	□	□	□	□	□	□	□

Sawn
Soft annealed plate/Unmachined

Thickness	Width
According to plate thickness	Within plate width

Uddeholm UHB 11 Stock Standard

Pre-machined

Tolerances: Thickness: -0/+0.2 mm Width: -0/+0.4 mm Length: 1030 mm

Width mm	Thickness, mm													
	4	6	8	10	12	16	20	25	32	40	50	63	80	100
25	■	■	■	■	■	■	■							
32	■	■	■	■	■	■	■	■						
40	■	■	■	■	■	■	■	■	■					
50	■	■	■	■	■	■	■	■	■	■				
63	■	■	■	■	■	■	■	■	■	■	■			
80	■	■	■	■	■	■	■	■	■	■	■	■		
100	■	■	■	■	■	■	■	■	■	■	■	■	■	
125		■	■	■	■	■	■	■	■	■	■	■	■	
160		■	■	■	■	■	■	■	■	■	■	■		
200		■	■	■	■	■	■	■	■	■	■			
250		■	■	■	■	■	■	■	■	■	■			
315			■	■	■	■	■	■	■	■	■			
350					■	■	■	■						
400	■	■	■	■	■	■	■	■						
Square				n	n	n	n	n	n	n	n	n	n	n

Uddeholm UHB 11 Stock Standard

Pre-Machined

Tolerances: Thickness: -0/+0.2 mm Width: -0/+0.4 mm

Random length: 1800-2000 mm

Line ground

Width mm	Thickness mm								
	20	25	32	40	50	63	80	100	125
160							☐	☐	
200			☐	☐	☐	☐	☐	☐	
250		☐	☐	☐	☐	☐	☐	☐	
300				☐	☐	☐			
315				☐	☐	☐	☐		
350				☐	☐	☐	☐	☐	☐
400			☐	☐	☐	☐	☐	☐	☐
450			☐	☐	☐	☐	☐	☐	
500	☐	☐	☐	☐	☐	☐	☐	☐	☐
550		☐	☐	☐	☐	☐		☐	
600		☐	☐	☐	☐	☐	☐	☐	