

Uddeholm Vanadis 30 SuperClean Stock Standard

Flat bar

Soft annealed/Unmachined

Soft annealed/Rough machined

mm	17	20	22	30	35	43	50	54	55	66	102
45		<input type="checkbox"/>									
95											
200	<input type="checkbox"/>										
208			<input type="checkbox"/>	<input type="checkbox"/>							
210		<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>		<input type="checkbox"/>			
260					<input type="checkbox"/>				<input type="checkbox"/>		
350											<input type="checkbox"/>
380							<input type="checkbox"/>				
600										<input type="checkbox"/>	

Square bar

Soft annealed/Unmachined

Soft annealed/Rough machined

mm	28	102
	<input type="checkbox"/>	<input type="checkbox"/>

Uddeholm Vanadis 30 SuperClean Stock Standard

Round bar

Soft annealed/Precision machined

Cold drawn fix length

Tolerance ISO h9

mm	8,3	10,3	12,3	13,0	14,0	15,0
	●	●	●	●	●	●

Round bar

Soft annealed/Rough machined

mm	16	18	20	22	26	30	35	40	46	48	52	60	70	82,6	85	110	130	140	150	160	170	290	
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●