

Uddeholm Vanadis 23 SuperClean Stock Standard

Flat bar

Soft annealed/Unmachined ☐

Soft annealed/Rough machined ■

mm	12	15	16	18	20	22	26	27	28	30	34	35	38	40	43	50	54	55	63	76,2	100	102	152	200	
57	☐					☐			☐																
83								☐																	
100																									
102																									
108	☐	☐		☐		☐			☐			☐			☐		☐								
150														☐		☐			■						
152,4																				■					
158				☐		☐			☐			☐					☐								
202																								■	
203								■					■		■										
203,2																							■		
210			☐	☐		☐			☐			☐			☐			■							
260			☐	☐	☐				☐								☐								
305																				■		■			
380														■		■									
400																								■	
450										■															
550																						■			

Uddeholm Vanadis 23 SuperClean Stock Standard

Square bar

Soft annealed/Unmachined □

Soft annealed/Rough machined ■

mm	20	43	50	57	69	120
	□	□	□	□	□	■

Round bar

Soft annealed/Precision machined

Cold drawn fix length/Tolerance ISO h9

mm	3,3	4,3	5,3	6,3	7,3	8,3	9,3	10,3	12,3	13,3	15,0
	○	○	○	○	○	○	○	○	○	○	○

Round bar

Soft annealed/Rough machined

mm	14	16	18	20	22	24	26	28	30	32	35	38	40	42	46	50,8	52	54	60	63,5
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	65	70	76,2	80	85	90	100	102	110	115	120	125	130	140	150	160	170	180
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	190	203	225	250	270	305	370	420
	●	●	●	●	●	●	●	●

Uddeholm Vanadis 23 SuperClean Stock Standard

Plate

Width: 1,00-4,99 = 650 mm, 5,00-80,00 = 750 mm

Tolerance: -0 / +200 mm

Length: Random length mm

Soft annealed/Unmachined

Thickness, mm	5,2	6,2	9,2	11,2	13,2	21	28	34
	☐	☐	☐	☐	☐	☐	☐	☐

Pre-machined

Tolerances: Thickness: +0,4+0,65 mm Width: +0,4/+0,8 mm

Random length: 1,2-3,0 m

Width mm	Thickness, mm										
	8	10	13	16	18	20	22	25	32	40	50
50											
100		☐				☐		☐		☐	
200									☐		
203			☐	☐	☐		☐				
252				☐	☐						