

## Uddeholm Stavax ESR Stock Standard

### Flat bar

Soft annealed/Unmachined

mm	11	12,7	20	22	25	28	35	38,1	40	43	54
45	<input type="checkbox"/>										
65							<input type="checkbox"/>				
75			<input type="checkbox"/>						<input type="checkbox"/>		
85						<input type="checkbox"/>					
90									<input type="checkbox"/>		
102		<input type="checkbox"/>						<input type="checkbox"/>			
105						<input type="checkbox"/>					
155				<input type="checkbox"/>							
166						<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>	<input type="checkbox"/>
206						<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>	<input type="checkbox"/>
228					<input type="checkbox"/>						
256						<input type="checkbox"/>	<input type="checkbox"/>			<input type="checkbox"/>	<input type="checkbox"/>
306										<input type="checkbox"/>	

The stock standard might change without notice

Issue date  
February, 2018  
1 (4)

## Uddeholm Stavax ESR Stock Standard

### Flat bar

Soft annealed/Rough machined

mm	38	40	50	51	63	64	76,2	80	89	90	100	114	127	153	160	178	203	254
102				■														
153							■											
160					■													
200					■			■										
228			■															
250					■			■										
300								■										
305	■			■		■	■			■			■	■				
350		■	■		■			■			■							
400		■	■		■			■			■							
450		■						■										
457	■			■		■							■					
500		■	■		■			■										
508																		
600															■			
610							■		■			■	■	■			■	■
762	■					■										■		

The stock standard might change without notice

Issue date  
February, 2018  
2 (4)

## Uddeholm Stavax ESR Stock Standard

### Round bar

Soft annealed bar/Unmachined 0

Soft annealed bar/Rough machined ●

mm	12,7	16	20	28	35	40	41	43	50,8	57,2	63,5	76,2	80	90	102	115	127	140	153	160	180	203	230	254	
	0	0	0	0	0	●	0	0	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Soft annealed/Precision machined

mm	10	30	45
	●	●	●

### Square

Soft annealed/Unmachined

mm	57	75
	□	□

## Uddeholm Stavax ESR Stock Standard

### Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.8 mm

Length: 1030 mm

mm	30	40	50	60	80	100
100	■	■	■	■	■	■
125	■	■	■	■	■	■
160	■	■	■	■	■	■
200	■	■	■	■	■	■
250		■	■	■	■	■
300		■	■	■	■	■