

Uddeholm Vanadis 23 SuperClean Stock Standard

Flat bar

Soft annealed/Unmachined □

Soft annealed/Rough machined ■

mm	10	12	15	18	20	22	27	28	35	40	41	43	45	50	54	63	76,2	80	100	102	200	
57	□	□	□	□		□		□			□											
100																						
102																		■				
108		□	□	□		□		□	□			□			□							
150										□				□		■						
152,4																	■					
158						□		□	□						□							
203,2																	■					
210						□		□	□			□					■					
260					□			□							□							
305																	■				■	
380										■												
400																						■
550																			■			

Square bar

Soft annealed/Unmachined □

Soft annealed/Rough machined ■

mm	20	43	50	57	69	86	120
	□	□	□	□	□	□	■

Uddeholm Vanadis 23 SuperClean Stock Standard

Round bar

Soft annealed/Precision machined
Cold drawn fix length/Tolerance ISO h9

mm	4,3	5,3	6,3	7,3	8,3	9,3	10,3	12,3	13,3	15,0
	○	○	○	○	○	○	○	○	○	○

Round bar

Soft annealed/Rough machined

mm	16	18	20	22	24	26	28	30	32	35	38	40	42	46	50,8	52	54	60	63,5	65
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	70	76,2	80	82,6	85	90	100	102	110	115	120	125	130	140	150	153	160	170	180	190
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

mm	203	210	225	250	270	305	370	420
	●	●	●	●	●	●	●	●

Plate

Width: 1,00-4,99 = 650 mm, 5,00-80,00 = 750 mm

Tolerance: -0 / +200 mm

Length: Random length mm

Soft annealed/Unmachined

Thickness, mm	5,2	6,2	9,2	11,2	13,2	21	28	34
	□	□	□	□	□	□	□	□

Uddeholm Vanadis 23 SuperClean Stock Standard

Pre-machined

Tolerances: Thickness: +0.4/+0.65 mm Width: +0.4/+0.80 mm

Random length: 1800-2000 mm

Width mm	Thickness mm							
	8	10	16	20	25	32	40	50
50	□	□	□	□				
100		□	□	□	□	□	□	□
200				□	□	□	□	
Square								□